



MOUNTAINSILOS

MINI HAY WRAPPERS

MOUNTAINSILOS 550 AV/550 AVE

Mini wrapping machine designed to wrap cylindrical forage bales. It is **suitable for walk-behind tractors of all kinds and makes.**

Wrapping is completely automatic.

A practical electrically powered wrapper version is also available, MOUNTAINSILOS 550 AVE, for working in closed spaces.

STRENGTHS

The mini wrapper MOUNTAINSILOS 550 AV represents the natural evolution of the agriculture mechanization. It is a small machine that wraps forage in cylindrical bales. The mini wrapper is suitable for single-axle walk-behind tractors of all makes and models. Bales are wrapped by means of the power unit PTO through a quick-coupling flange.

Wrapping is completely automatic: the operator just needs to set the number of wrappings per bale and pull the START lever. After wrapping the machine stops automatically. A practical electrically powered version is also available, MOUNTAINSILOS 550 AVE, for working in closed spaces.

TECHNICAL DATA

Machine weight	89 kg
Plastic film: - width	25 cm
- length	1,800 m
Film stretching	50%
Lap winding	6/4/2
Wrapping capacity: bale height	52 ÷ 73 cm
Bale Ø	50 ÷ 60 cm
Bale weight	40 ÷ 50 kg



MOUNTAINSILOS 550 AV / 550 AVE



MOUNTAINSILOS 550 ATP

Mini wrappers trailed by **small tractors.**

STRENGTHS

MOUNTAINSILOS 550 ATP is a small machine that wraps small cylindrical bales of forage with film to turn it into silage. Its special design makes it possible **to hook it up to all types of tractors by means of a three-point linkage.** It is driven by the tractor PTO via cardan shaft transmission.

The wrapping of the bales is fully automatic: the operator only needs to set the type of wrapping he wishes (the film can be wrapped around the bale 2/4/6 times) and then pull the START lever.

The machine stops automatically once the bale has been wrapped.

TECHNICAL DATA

Machine weight	93 kg
Plastic film: - width	25 cm
- length	1,800 m
Film stretching	50%
Lap winding	6/4/2
Wrapping capacity: bale height	52 ÷ 73 cm
Bale Ø	50 ÷ 60 cm
Bale weight	40 ÷ 50 kg



MOUNTAINSILOS 550 ATP

CAEB INTERNATIONAL srl
via Botta Bassa, 22 - 24010 Petosino di Sorisole (BG) - Italy
tel. +39 035 570451 - fax +39 035 4129105 - info@caebinternational.it - www.caebinternational.it





MINICARGO

CARRIAGES FOR TRANSPORTING HAY BALES AND OTHER MATERIALS

Carriages linkable to all kinds of **walk-behind tractors and reversible motocultivators** simply by replacing a flange.

The MINICARGO carriages can be equipped with different wagons to transport any kind of material such as, for example, timber.

STRENGTHS

MINICARGO is a range of carriages that can be linked to **all kinds of walk-behind tractors and reversible motocultivators** by replacing a flange. The carriages MINICARGO take advantage of their easy, quick steering motion as well as of their low centre of gravity to assure a good stability. Thanks to their small dimensions, handiness and high loading capacity the MINICARGO carriages are particularly suitable for **hilly and mountainous areas**. The two MINICARGO versions have a different wagon, that can easily be replaced depending on the operator's specific needs.

The MINICARGO carriages are equipped with a special system that allows to easily tip big quantities of heavy material. Their unique four-wheeled support allows the operator to easily operate without sustaining the machine. The front wheels are controlled by a handy, quick-acting steering which avoids any effort to the driver.

The MINICARGO carriages are linked on the front, so that the weight can act on the rear driving wheels and therefore have a better grip on the ground when the machine is working uphill.

TECHNICAL DATA

MINICARGO MCL

Carrying capacity	up to 300 kg
Tubular steel frame	50 x 50 x 3 mm
Wheels	bearing-supported direction wheels 3.50.8 PR 4
Front steering	with bearing-supported motion
Tipping	on the front, manual
Central rocking joint	with 15° of longitudinal tilt
Platform width	1,000 mm
Platform length	670 mm

REMARK

It is advisable to fit brakes.

MINICARGO MCM

Carrying capacity	up to 400 kg
Capacity	220 l
Tubular steel frame	50 x 50 x 3 mm
Wheels	bearing-supported direction wheels 3.50.8 PR 4
Front steering	with bearing-supported motion
Tipping	on the front, manual
Central rocking joint	with 15° of longitudinal tilt



MINICARGO MCL



MINICARGO MCM

CAEB INTERNATIONAL srl
via Botta Bassa, 22 - 24010 Petosino di Sorisole (BG) - Italy
tel. +39 035 570451 - fax +39 035 4129105 - info@caebinternational.it - www.caebinternational.it

